



References

Serie Model
DU

Dimensions & Weight

Height	Width	Length	Net Weight	Volume
85 mm	150 mm	158 mm	1.53 Kg	2.015 L
Box height	Box width	Box length	Gross weight	Gross volume
115 mm	180 mm	300 mm	1.98 Kg	6.21 L

Design

Usage	Color	ARGB
Gaming/Work Station	Black	No

General Data

Continuous power	Peak Power	Form Factor	Modularity	Wire-free design
500W	550W	ATX 2.0	Non modular	No
Input Voltage (Vac)	Input Frequency	Input current	PFC	Sand-by Power
100-240	50-60	15-5A	PFC	<0.5
Average life time (h / 25°C)	Operating temperature up to (°C)			
>50000	0-45°C			

Output

12V rails (multi-rail operation)	12V single rail operation	Overclocking key	+3.3V	+12V1
1	Yes	No	15, 0,5	38 A
+5Vsb	Max. combined power 12V	Max. combined power 3.3V + 5V	Hold-up time at 100% load	Power good signal
2.5 A	456 W	100 W	16	100-500

Cooling technology

Fan type	+SilentWings	Motor technology	Bearing technology	Fan size
DC Fan	Yes	Brushless DC fan	Hydraulic Bearing	140*25
Max. fan speed (rpm), temperature-dependent	Temperature control for case fans	dB(A) at 20% load	dB(A) at 50% load	dB(A) at 100% load
2000 rpm	Yes	22.5	26.22	35.16

Protection

OCP (over current protection)	OVP (over Voltage protection)	UVP (under Voltage protection)	SCP (short circuit protection)	OTP (over temperature protection)
Yes	Yes	Yes	Yes	Yes
OPP (over power protection)	SIP (Surge & Inrush Protection)			
Yes	Yes			

Safety certification

CE Yes	CB Yes	TÜV Yes	FCC Yes	cRUus No
cTUVus Yes	RCM (Australia) No	BSMI No	CU (Russia) No	CCC No

Eco Efficiency

80 PLUS certification
80+ BRONZE

Environmental directives

Energy Star No	ErP No	WEEE Yes	RoHs Yes
-------------------	-----------	-------------	-------------

Connectors

Cable management Non modular	Cables type wired mesh shield cable + flat wire	Flat cables Yes	All-in-one cable (SATA/PATA/FDD) No	No. of cables Direct 6pcs
ATX-Motherboard (20+4-pin) 1	P4+4 (CPU) 1	PCI-e 6+2-pin (GPU) 2	PATA 3	SATA 5

Accessories

Screws 4	Cable ties 2	Box/Bag for PSU/Cables Yes	SFX-to-ATX adapter bracket No
-------------	-----------------	-------------------------------	----------------------------------

Warranty & Docs

Commercial Warranty
5 années

